



Material Safety Data Sheet

Revised 13 October 2010

Section 1 - Product and Company Identification

Product Name:	Woodwright Apex	Emergency Phone:	1-800-322-8172
Product Codes:	9988		(Monday - Friday, 7:30 a.m. to 5:00 p.m. EST)
Manufacturer:	David E. Easterday & Company, Inc.	Chemtrec Phone:	1-800-424-9300
Address:	P.O. Box 332	Other Calls:	(330) 359-0700
	Mount Eaton, Ohio 44659	Facsimile:	(330) 359-0800

Section 2 - Composition/Information on Ingredients

<u>Ingredient</u>	<u>CAS No.</u>	<u>HAP (Y/N)</u>	<u>VOC (Y/N)</u>	<u>% by Wt.</u>
n-butyl acetate	123-86-4	No	Yes	29
ethyl alcohol	64-17-5	No	Yes	14
acetone	67-64-1	No	No	11
isopropyl alcohol	67-63-0	No	Yes	3
2-butoxyethanol	111-76-2	No	Yes	3
bis(2-ethylhexyl)-1,4-benzenedicarboxylate	6422-86-2	No	Yes	1
methyl propyl ketone	107-87-9	No	Yes	1
xylene	1330-20-7	Yes	Yes	< 1
formaldehyde	50-00-0	Yes	Yes	< 0.1
ethyl benzene	100-41-4	Yes	Yes	< 0.1
methanol	67-56-1	Yes	Yes	< 0.1

Section 3 - Hazards Identification

Emergency Overview: This product is an opaque liquid with a strong solvent odor. Inhalation overexposure to the vapors of this product can cause severe respiratory irritation, dizziness, weakness, fatigue, nausea, headache and possible unconsciousness. A component of this product is suspected to be carcinogenic and teratogenic in humans. This product is flammable and can be readily ignited under normal ambient conditions. Vapors of this product may travel to a source of ignition and flashback to a leak or open container. If involved in a fire, this product will release smoke and toxic gases (i.e., carbon monoxide, carbon dioxide). This product is not reactive. Emergency responders must wear proper personal protective equipment suitable for the situation to which they are responding.

Routes of Entry: Inhalation, Skin Absorption, Ingestion. Skin Contact. Eye Contact.

Inhalation - Can cause severe respiratory irritation, dizziness, weakness, fatigue, nausea, headache and

possible unconsciousness. Irritation may be delayed for several hours.

- Skin Absorbtion -** Can be absorbed through the skin but exposure must be extensive before adverse health effects occur. Can be toxic if absorbed through the skin; may cause target organ damage. Minimal hazard in normal industrial use. May cause gastrointestinal discomfort.
- Ingestion -** Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal. Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea.
- Skin Contact -** Moderately irritation to the skin. Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.
- Eye Contact -** Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue. Contact with the eyes may cause moderate to severe eye injury. Temporary vision impairment (cloudy or blurred vision) is possible.
- Medical Conditions Aggravated:** May aggravate pre-existing skin disorders, respiratory disorders, kidney disease, liver disease, eye disorders, and or gastrointestinal disorders.

- Carcinogenicity:**
- | | |
|-----------------------------|--|
| NTP Carcinogen - | Yes (formaldehyde gas - reasonably anticipated to be a human carcinogen) |
| IARC Monographs - | Yes (2-butoxyethanol - Group 3, not classifiable as to carcinogenicity)
Yes (ethanol - Group 1 - carcinogenic to humans)
Yes (xylene - Group 3, not classifiable as to carcinogenicity)
Yes (ethylbenzene - Group 2B, possibly carcinogenic to humans)
Yes (formaldehyde - nasopharyngeal, leukemia, sinonasal) |
| OSHA Regulated -
NIOSH - | Yes (formaldehyde - 29CFR1910.1048)
Yes (formaldehyde - A2, suspected human carcinogen) |
- Teratogenicity:** Possible reproductive hazard. A component in this product has been shown to cause birth defects and reproductive disorders in laboratory animals at doses that could be encountered in the workplace.
- Mutagenicity:** No data available to indicate product or any components present at greater than 0.1% is mutagenic.

Section 4 - First Aid Measures

- Inhalation:** Move victim to fresh air. If not breathing, call 911 (or emergency services number if 911 service is not available) and administer artificial respiration. If breathing is difficult, have a trained individual administer oxygen. Get medical attention immediately.
- Eyes:** Immediately flush eyes with plenty of water for at least 20 minutes - opening and closing eyelids often. Get medical attention immediately.
- Skin Contact:** Wash with mild soap and water. If clothing is contaminated, remove contaminated clothing being careful to avoid additional skin contact. Wash contaminated clothing before reuse. Get medical attention if irritation develops or persists.
- Ingestion:** Do not induce vomiting. Call 911 (or emergency services number if 911 service is not available). Get medical attention immediately.

storage should be implemented.

Eyes - Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Do not wear contact lenses. Have an eye wash station available.

Skin - Avoid skin contact by wearing chemically resistant gloves, an apron and other protective equipment depending upon conditions of use. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving the jobsite.

Section 9 - Physical and Chemical Properties

Physical State	liquid
Odor	strong solvent
Solids, Wt % (calc.)	35.56
Material VOC, lbs/gal (calc.)	4.24 (actual)
Coating VOC, lbs/gal (calc.)	4.88 (regulatory)
Weight per gallon (calc.)	7.91
VHAPs, lbs/lb of solids (calc.)	0.02
lbs VOC/lb solids (calc.)	1.51

Section 10 - Stability and Reactivity

Stability: Spontaneous combustion can occur. Stable under normal conditions.

Conditions to Avoid: Heat, sparks, open flames or other sources of ignition.

Incompatibility (Materials to Avoid): Strong oxidizing agents. Strong acids. Peroxides.

Hazardous Decomposition or Byproducts: Carbon monoxide, Carbon dioxide.

Hazardous Polymerization: Will not occur.

Section 11 - Toxicological Information

<u>Ingredient</u>	<u>CAS No.</u>	<u>LC₅₀/LD₅₀/IDLH</u>
n-butyl acetate	123-86-4	LC50 Rat - 160 ppm to 2,000 ppm/4 hrs; IDLH - 1,700 ppm
2-butoxyethanol	111-76-2	LC50 Rat - 450 ppm/4 hrs; LD50 Rat - 470 mg/kg to 1,480 mg/kg; IDLH - 700 ppm
isopropyl alcohol	67-63-0	LC50 Rat - 12,000 ppm/8 hrs; LD50 Rat - 5,045 mg/kg; IDLH - 2,000 ppm
xylene	1330-20-7	LC50 Rat - 5,000 ppm/4 hrs; LCLo Human - 6125 ppm/12 hrs; IDLH - 900 ppm
acetone	67-64-1	LC50 Rat - 20,702 ppm/8 hrs; LD50 Rat - 5,800 mg/kg; IDLH - 2,500 ppm

ethyl benzene	100-41-4	LCLo Rat - 4,000 ppm/4 hrs; IDLH - 800 ppm
methanol	65-56-1	LD50 Rat - 12,880 mg/kg; LD50 Rabbit - 14,200 mg/kg; IDLH - 6,000 ppm
formaldehyde	50-00-0	LC50 Rat - 815 ppm/30 min; LC50 Mouse - 333 ppm/2 hrs; LD50 Rat - 100 mg/kg; LD50 Rabbit - 270 mg/kg; IDLH - 20 ppm
methyl propyl ketone	107-87-9	LD50 Rat - 1,600 mg/kg; LD50 Mouse - 1,600 mg/kg; IDLH - 1,500 ppm

Target Organ Acute Toxicity

n-butyl acetate	eyes, skin, respiratory system, CNS
2-butoxyethanol	eyes, skin, respiratory system, CNS, blood, liver, kidneys
isopropyl alcohol	eyes, skin, respiratory system
xylene	eyes, skin, respiratory system, CNS, gastrointestinal tract, blood, liver, kidneys
acetone	eyes, respiratory system, CNS, liver, kidneys, gastrointestinal tract
ethyl benzene	eyes, skin, respiratory system, CNS
methanol	eyes, skin, respiratory system, CNS
formaldehyde	eyes, skin, respiratory system
methyl propyl ketone	eyes, skin, respiratory system, CNS

Section 12 - Ecological Information

Overview: No data available. No ecological information available.

Section 13 - Disposal Considerations

Waste Disposal Method: Whatever cannot be recovered, reused, or recycled in an appropriate manner should be disposed of at an approved waste facility. Processing, use or contamination of this product may change the waste management options. Dispose of container and unused contents in accordance with applicable federal, state and local laws and regulations.

EPA: If disposed, this coating is considered a RCRA ignitable waste, D001.

Components Subject to EPA Land Ban Restrictions:

acetone	67-64-1
xylene	1330-20-7
ethyl benzene	100-41-4
formaldehyde	50-00-0

Section 14 - Transportation Information

U.S. Department of Transportation Title 49 CFR, Subchapter C	Proper Shipping Name: Hazard Class: I.D. Number: Packing Group:	Paint 3 UN 1263 II
Emergency Response Guidebook (2008)	Guide Number:	128

Section 15 - Regulatory Information

Sara 313 Reportable:

<u>Chemical</u>	<u>CAS No.</u>
acetone	67-64-1
xylene	1330-20-7
ethyl benzene	100-41-4
formaldehyde	50-00-0
methanol	107-87-9

Section 16 - Other Information

To the best of our knowledge, the information and recommendations contained herein were believed to be accurate at the time of preparation, or obtained from sources believed to be reliable. However, it is the user's responsibility to determine safety, toxicity, and suitability for his own use of the product. No warranties of any kind, either expressed or implied, including fitness for a particular purpose, are made regarding the product described, data or information set forth. In no case shall the descriptions, information or data provided be considered as part of our terms and conditions of sale. The descriptions, information and data furnished herein are given gratis. No obligation or liability for the descriptions, information and data given are assumed. All such being given and accepted at your risk.

The customer or recipient of this MSDS should ensure that the information contained in this MSDS is made available to all employees or other persons whom he knows or believes will use this material.